

# Neschen ColdLam1650

valid from: 2023-06-13

### PRODUCT INFORMATION

- the Neschen ColdLam 1650 PLUS is a pressure sensitive machine with heat assist on the top roller (70 degrees) to provide superb results with a wide range of materials.
- Regardless of the user's experience, the Neschen ColdLam 1650 PLUS is easy to operate and offers real flexibility and high performance levels for small and medium-sized end user.
- due to the excellent price-performance ratio, the Coldlam 1650 PLUS laminator is particularly suitable for advertising technicians.
- the machine offers these users more diverse image enhancement options and thus increases their profitability.
- this laminator is also suitable for small to medium display based businesses who want to provide a wider range of applications and have no need for a machine with shrink-wrapping options.

### Optimum performance

- 1650 mm working width to cope with a wide range of media
- 8 m/min maximum speed for improved productivity
- fully adjustable air pressure and speed settings for maximum versatility
- 40 mm nip opening to cover a wide range of substrates
- electrical nip adjustment for precise operation
- heat assisted top roller (70°C) for excellent lamination performance
- robust, free-standing design

### Ease of use

- flip up infeed table to facilitate easy setup
- in-feed roll trough
- ergonomic control panel for ease of use
- additional control panel at the rear of the machine
- auto grip material holders for user-friendly material loading
- roll-to-roll built-in
- externally arranged brakes for better adjustment of the film tension on the material holders
- one storage compartment per side for user needs
- levelling feet

### POPULAR APPLICATIONS

- rigid Indoor & Outdoor Display Media
- flexible Indoor & Outdoor Display Media
- Floor Graphics Media
- Roll-Up Display Media
- Backlit Display Media
- Pop-Up Display Media
- all kinds of poster- and art prints
- further information and an overview of all Neschen products is available at: [www.atech.co.uk](http://www.atech.co.uk)

### Safety

- foot switch for hands free operation
- self-checking safety eyes for increased operator safety
- removable safety guide
- CE-certified



### Neschen ColdLam1650

valid from: 2023-06-13

<b>Maximum Working Width</b>	1650 mm
<b>Maximum Speed</b>	8 m/min
<b>Nip pressure</b>	1,6 N/mm
<b>Maximum Substrate Thickness</b>	40 mm
<b>Roller Heating</b>	heated upper roller
<b>Maximum Roller Temperature</b>	70 °C
<b>Width</b>	2175 mm
<b>Height</b>	1320 mm
<b>Depth</b>	550 mm
<b>Depth (incl. In-feed table)</b>	750 mm
<b>Table Height</b>	870 mm on wheels, adjustable to 950 mm
<b>Machine Weight</b>	400 kg
<b>Shipping Weight</b>	470 kg
<b>Shipping Dimensions</b>	Width 2300 mm Height 1550mm Depth 1000mm
<b>Electrical Requirements</b>	1N/PE 230VAC/50-60 Hz; 1700W 8A

#### ITEM CODE - **6037409 PLUS**

Published information concerning our products is based upon practical knowledge and experience. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. The purchaser must assume all risks for any use, operation and application of the material. We are liable for damage only upon the amount of the purchase price under exclusion of indirect and accidental damage. All information given serves only to describe the product and is not to be regarded as assured properties in the legal sense. Specifications subject to change without notice, errors and omissions excepted. The German version is solely and exclusively valid and legally binding.

